

06-16-00

Attorney Docket No. P00,0954

First Named Inventor or Application Identifier

Georg-Erwin Arndt et al,

Express Mail Label No: # EL568800011US

A
00/ST/90
P-10
c633 U.S. PTO
09/54393
06/15/00UTILITY
PATENT APPLICATION
TRANSMITTALOnly for new nonprovisional applications under 37 CFR
1.53(b)ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. Specification [Total Pages 12]
 2. Drawing(s) (35 USC 113) [Total Pages 2]
 3. Declaration and Power of Attorney [Total Pages 2]
 a. Newly executed declaration (Original copy)
 b. Copy from prior application (37 CFR 1.63(d))
 (for continuation/divisional with Box 14 completed)
 [Note Box 4 Below]
 i. DELETION OF INVENTOR(S)
 Signed statement attached deleting
 Inventor(s) named in the prior application,
 see 37 CFR 1.63(d)(2) and 1.33(b).
 4. Incorporation By Reference (useable if Box 3b is checked)
 The entire disclosure of the prior application, from which a
 copy of the oath or declaration is supplied under Box 3b,
 is considered as being part of the disclosure of the
 accompanying application and is hereby incorporated by
 reference therein.

ACCOMPANYING APPLICATION PARTS

5. Assignment Papers (cover sheet & documentation)
 Siemens Audiologische Technik GmbH.
 6. Letter under 37 CFR 1.41(c).
 7. English Translation Document (if applicable)
 8. Information Disclosure Statement (IDS)/PTO-1449
 9. Preliminary Amendment
 10. Return Receipt Postcard (MPEP 503)
 (Should be specifically itemized)
 11. Small Entity Statement filed in prior application,
 Statement(s) Status still proper and desired
 12. Certified Copy of Priority Document(s) German
 Application No. 199 27 278.6 filed June 15, 1999
 13. Other:

14. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information.

Continuation Divisional Continuation-in-part (CIP) of prior application No: /


CLAIMS AS FILED

	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) BASIC FEE \$690.00
TOTAL CLAIMS	20	10			
INDEPENDENT CLAIMS	3	2			
	ANY MULTIPLE DEPENDENT CLAIMS? (Y)ES (X) NO				
				TOTAL FILING FEE ->	\$690.00

 The Commissioner is hereby authorized to charge any additional fees which may be required in connection with this application, or credit any overpayment to ACCOUNT NO. 08-2290. A duplicate copy of this sheet is enclosed. A check in the amount of \$ 690.00 to cover the filing fee is enclosed.

15. CORRESPONDENCE ADDRESS

HILL & SIMPSON
 A Professional Corporation
 233 South Wacker Drive - 85th Floor Sears Tower
 Chicago, Illinois 60606
 Telephone (312) 876-0200 Fax (312) 876-0898

SIGNATURE: 

491/899:1190

U-11

DATE: June 15, 2000

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" Mailing Label Number **EL 568800011US**
Date of Deposit: June 15, 2000

jc833 U.S. PTO
09/594393
06/15/00



I hereby certify that the following is being deposited with the United States Postal "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Proposed Patent Application for GEORG ERWIN ARNDT, HARTMUT RITTER, and ANTON GEBERT entitled "METHOD FOR ADAPTING A HEARING AID, AND HEARING AID WITH A DIRECTIONAL MICROPHONE ARRANGEMENT FOR IMPLEMENTING THE METHOD", consisting of specification, claims, 2 sheets of informal drawings, and Government Filing Fee, Attorney Docket No. P00,0954


Signature of person
mailing application

Leo Donlin
Name of person mailing
application

S P E C I F I C A T I O N

TITLE

**"METHOD FOR ADAPTING A HEARING AID, AND HEARING AID WITH
A DIRECTIONAL MICROPHONE ARRANGEMENT FOR
IMPLEMENTING THE METHOD"**

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a method for adapting a hearing aid and to a hearing aid arrangement operating according to the method.

Description of the Prior Art

Hearing aids with a directional microphone arrangement that is formed by at least two omnidirectional microphones are known as prior art, wherein differences in the signal transmission behavior of the utilized microphones are corrected by means of filters that are connected downstream of the microphone.

Further, it is known to adapt a hearing aid with directional microphones to a person wearing a hearing aid device with the aid of the artificial head "KEMAR" ("Knowles Electronics Manikin for Acoustical Research") that is based on the average anatomy of a user.

A disadvantage of these known hearing aids is that they often achieve an insufficient directivity.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a method for improving the directivity of a hearing aid that is worn at the head as well as to provide a hearing aid arrangement to improve the directivity of a hearing aid.

The above object is achieved in accordance with the principles of the present invention in a method for adapting a hearing aid having a number of microphones which, in combination, produce a directional characteristic, and having respective filters connected downstream from the microphones which can be parameterized, as well as a signal processing stage and an earphone, and wherein the hearing aid is arranged at the head of a user and is exposed to acoustic waves from different directions, wherein the microphones convert the received acoustic signals into electrical signals which are supplied to an external measuring and evaluation unit, and wherein, in the measuring and evaluation unit, filter parameters are calculated from the electrical signals and are supplied to the hearing aid so as to parameterize the filters in terms of amplitude response and/or frequency response, to optimize the directional characteristic.

The directional characteristic of a hearing aid with a directional microphone can be determined by an appropriate measuring arrangement in a room for precision measuring. The position of the sound angles of incidence, at which the input signal is completely erased (erasure points), is the determining factor with respect to the thus-acquired directional diagrams. Different factors compete with an ideal directivity:

- microphones that are connected to one another for purposes of generating a directional characteristic differ in their frequency responses.
- external, individual conditions with respect to wearing the hearing aid have a negative effect on the desired directivity.

Whereas known methods only compensate the different transmission behavior of the utilized microphones and whereas the influence of a person wearing a hearing aid

HR 66.2000
Am 6.6.2000
Ec 6.6.2000

on the directional characteristic is only considered in the form of an artificial head that is adapted to the average anatomy of a user given the KEMAR method, the inventive method also takes individual conditions in connection with the person wearing the hearing device into consideration in order to improve the directivity. For example, individual conditions are the shape of the head, the size and physical nature of the external ear, the wearing position of the hearing aid device, the presence of eye glasses etc.. The frequency responses of the signals received by the microphones that are disturbed by these conditions lead to the displacement of the erasure points, assure that there is only a limited damping of the input signal at these points instead of an erasure. The invention minimizes the differences regarding the transmission behavior of the microphones, minimizes the aforementioned parasitic inductions and improves the directivity of the hearing aid.

The adjustment of the directional characteristic and the tuning of the microphones ensues by means of an "in-situ-measuring", i.e. the user wears the hearing aid containing the microphones, and the signal curves in the signal paths of the microphones are tuned to one another.

Advantageously, the hearing aid that is arranged at the head of a person is sequentially exposed to acoustic waves from different directions for acquiring a directional diagram. A measuring and evaluation unit calculates filter parameters therefrom, from which an approximation of the measured directional characteristic ensues with respect to the desired directional characteristic.

The determination of appropriate filter parameters can ensue once or in an iterative method by repeatedly measuring, and taking the filter parameters acquired in the previous measurement into account.

In another version of the method, the hearing aid arranged at the head of the person is simultaneously exposed to acoustic waves from different directions (diffuse control panel) and the amplitude responses and/or phase responses of the incoming signals at various angles of incidence from the microphone are registered. Although this method, requires a higher calculating outlay, a shorter measuring time results for determination of the directional characteristic and the filter parameters.

The inventive hearing aid has filters in the signal paths of the microphones, and an amplitude response adaptation and/or phase response adaptation of the signals recorded by the microphones can be carried out by means of adjustable filter parameters. Preferably, the amplitude and phase responses can be adjusted separately from one another in these filters. For example, an FIR (Finite Impulse Response) filter exhibits this property.

In certain hearing aid devices with directional microphones, different directional characteristics can be selected by selecting different hearing programs, for example. Depending on the desired directional characteristic, the user-dependent parasitic inductions occur differently. In a further version of the invention, different sets of filter parameters are therefore acquired for eliminating the respective parasitic inductions in a hearing aid having a number of adjustable directional characteristics. These sets of filter parameters are stored in the hearing aid and are activated automatically by switching or by the user.

DESCRIPTION OF THE DRAWINGS

Figure 1 shows a measuring and evaluation unit in an arrangement for adapting a hearing aid worn at the head of a person.

Figure 2 is a block diagram of a hearing aid arrangement constructed and operating in accordance with the invention, with a hearing aid having microphones for generating a directional characteristic in connection with a measuring and evaluation unit of the type shown in Figure 1.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the measuring and evaluation arrangement shown in Figure 1, a hearing aid 1 worn at the head 8 of a person is situated in a room 10 for precision measuring (such as an anechoic chamber) for acoustic exposure from different directions with speakers 11, 12, 13 and 14 that can be individually driven and that can be modified with respect to their position to the hearing aid 1. An external measuring and evaluation unit 9, which is connected to the speakers via a signal path 15, controls the measurement. The sound signals recorded by the microphones 2, 3 of the hearing aid 1 are supplied via the signal path 16 of the external measuring and evaluation unit 9, which determines the directivity of the hearing aid device 1 dependent on the individual conditions. Normally, the measured directional diagram significantly differs from the desired ideal directional diagram. This is caused by a number of parasitic inductions, such as microphones that differ from one another with respect to their frequency responses wearing position of the hearing aid at the head, size and physical nature of the external ear, wearing eyeglasses etc. The measuring and evaluation unit 9 calculates filter parameters from the registered directional diagram. These filter parameters, via the

signal path 16, can be transferred to filters 4, 5 that can be parameterized and that are connected downstream with respect to the microphones 2, 3 of the hearing aid 1. The directional characteristic of the hearing aid device 1 that is adapted to the individual conditions in this way is now in better accordance with the desired ideal directional characteristic. A further approximation with respect to the ideal directional characteristic can be achieved by repeating this process, possibly by including the filter parameters acquired in the previous step and the thus-modified directional characteristic.

In the inventive hearing aid arrangement shown in Figure 2, the hearing aid 1 contains two microphones 2, 3 that are connected to one another (in a known way that is not shown) for generating a directional characteristic. Filters 4, 5 that can be parameterized are situated in the signal paths of the microphones 2, 3. The amplitude and phase responses of these filters 4, 5 can be adjusted independently of one another. For example, an FIR filter exhibits this property. The sound signals recorded by the microphones 2, 3 are supplied to a signal processing unit 6 for generating the directional characteristic and for the further processing and are finally emitted via an earphone 7. For calculating the filter parameters, the signals picked up by the microphones 2, 3, are tapped in the signal paths of the microphones 2,3, preferably after the parameterizable filters 4 and 5, and are supplied to the measuring and evaluation unit 9 via a signal path 17. In addition, the signals at the outputs of the microphones 2, 3 and at the input of the earphone 7, via two signal paths 18 and 19, are utilized for calculating the filter parameters in the exemplary embodiment. The frequency responses of the signals in the individual signal paths can be tuned to one another and, for example, the position of the sound angles of incidence, at which a

signal erasure ensues and which critically determine the directivity, can be adjusted by means of the filter parameters. The disturbing influence due to nonidentical microphones, the wearing position of the hearing aid 1 at the head, the size and physical nature of the external ear, etc. are minimized as a result thereof. The transmission of the filter parameters to the hearing aid 1 ensues via a signal path either directly by means of the measuring and evaluation unit 9 or by means of an external programming device (not shown). Moreover, the filter parameters can be stored in an internal storage unit 21 of the hearing aid 1 in the exemplary embodiment. Therefore, a number f sets of filter parameters, for different directional characteristics, can be stored and can be activated if required, for example, for adapting to different hearing situations.

Although modifications and changes may be suggested by those skilled in the art, it is the intention of the inventors to embody within the patent warranted hereon all changes and modifications as reasonably and properly come within the scope of their contribution to the art.

WE CLAIM AS OUR INVENTION:

1. A method for adapting a hearing aid to user-dependent conditions, comprising the steps of:

providing a hearing aid device to be worn at an ear of a user, having a microphone arrangement with a directional characteristic comprising a plurality of microphones with filters respectively connected downstream therefrom, said filters being parameterizable in terms of amplitude response and phase response, and a signal processing stage and an earphone;

while said user is wearing said hearing aid, exposing said hearing aid to acoustic waves from different directions to produce incoming acoustic signals to said microphones, said microphones converting said incoming acoustic signals into electrical signals;

providing a measuring and evaluation unit externally from said hearing aid and supplying said electrical signals to said external measuring and evaluation unit;

in said measuring and evaluation unit, calculating filter parameters from said electrical signals; and

supplying said filter parameters from said measuring and evaluation unit to said filters in said hearing aid for setting at least one of said amplitude response and said phase response in each of said filters to optimize said directional characteristic.

2. A method as claimed in claim 1 wherein the step of exposing said hearing aid to acoustic waves from different directions comprises successively exposing said hearing aid to acoustic waves from respectively different directions in a sequence, and wherein the step of calculating said filter parameters comprises calculating said filter parameters in said measuring and evaluation unit after said sequence.

3. A method as claimed in claim 1 wherein the step of exposing said hearing aid to acoustic waves from different directions comprises successively exposing said hearing aid to acoustic waves from respectively different directions in a plurality of sequence, and wherein the step of calculating said filter parameters comprises calculating said filter parameters in said measuring and evaluation unit after each sequence.

4. A method as claimed in claim 1 wherein the step of exposing said hearing aid to acoustic waves from different directions comprises successively exposing said hearing aid to acoustic waves from respectively different directions in a plurality of sequence, and wherein the step of calculating said filter parameters comprises calculating said filter parameters in said measuring and evaluation unit after a prescribed number of said sequences.

5. A method as claimed in claim 1 wherein the step of exposing said hearing aid to acoustic waves from different directions comprises simultaneously exposing said hearing aid to acoustic waves from said different directions.

6. A hearing aid arrangement comprising:

a hearing aid having a directional characteristic, with a plurality of microphones and respective filters connected downstream from said microphones, a signal processor and an earphone, said filters being parameterizable with regard to amplitude response and phase response;

a measuring and evaluation unit disposed externally from said hearing aid and in communication at least with outputs from said microphones in said hearing aid and with said filters in said hearing aid, said measuring and evaluation unit receiving electrical signals from said microphones corresponding to acoustic signals received from different directions by said microphones while said hearing aid is being worn by a user, and said evaluation and measuring unit calculating filter parameters from said electrical signals and supplying said filter parameters to said filters in said hearing aid for adjusting at least one of said amplitude response and said phase response of said filters.

7. A hearing aid arrangement as claimed in claim 6 wherein each of said filters is a filter wherein said amplitude response and said phase response are independently adjustable.

8. A hearing aid arrangement as claimed in claim 7 wherein each of said filters is an FIR filter.

9. A hearing aid arrangement as claimed in claim 6 wherein said hearing aid further comprises a memory in which a plurality of different sets of filter parameters, calculated in said measuring and evaluation unit and supplied to said memory, are stored.

10. A hearing aid arrangement as claimed in claim 9 wherein said measuring and evaluation unit calculates said different sets of filter parameters respectively for different directional characteristics.

ABSTRACT OF THE DISCLOSURE

In a method for adapting a hearing aid, and a hearing aid arrangement for improving the directivity of a hearing aid with a number of microphones that are connected to one another for generating a directional characteristic, the hearing aid is exposed to acoustic waves in a room for precision measuring while the user is wearing it, and the directional characteristic is registered. The filter parameters that arise therefrom are supplied to parameterizable filters in the hearing aid that are connected downstream from the microphones, and the desired ideal directional characteristic can be approximated taking the individual conditions into account when the hearing aid is worn.




FIG 1




FIG 2

100-102.02

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

H

"METHOD FOR ADAPTING A HEARING AID, AND HEARING AID WITH A DIRECTIONAL MICROPHONE ARRANGEMENT FOR IMPLEMENTING THE METHOD"

R 6.6.2002

Ar 6.6.2002

U 6.6.2002

Case No. P00,0954, the specification of which

(check one) X is attached hereto.
— was filed on _____, as
Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent Office all information which is known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, 1.56(a).¹

I do not know and do not believe this invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and I believe that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as identified below:

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below

Prior Foreign Application(s) Number	Country	Date
--	---------	------

19927278.6	Fed. Rep. Of Germany	June 15, 1999
------------	----------------------	---------------

and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the above listed application on which priority is claimed:

¹ (b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and
(1) It establishes, by itself or in combination with other information, a *prima facie* case of unpatentability of a claim; or
(2) It refutes, or is inconsistent with, a position the applicant takes in:
(i) Opposing an argument of unpatentability relied on by the Office, or
(ii) Asserting an argument of patentability.

A *prima facie* case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

If no priority is claimed, I have identified all foreign patent applications filed prior to this application:
Prior Foreign Application(s)

And I hereby appoint Messrs. John D. Simpson (Registration No. 19,842), Dennis A. Gross (24,410), Robert M. Barrett (30,142), Steven H. Noll (28,982), Kevin W. Guynn (29,927), Robert M. Ward (26,517), Brett A. Valiquet (27,841), Edward A. Lehman (22,312), David R. Metzger (32,919), Todd S. Parkhurst (26,494), James D. Hobart (24,149), Melvin A. Robinson (31,870), Joseph P. Reagan (35,332), Michael R. Hull (35,902), Michael S. Leonard (37,557), William E. Vaughan (39,056) and Lewis T. Steadman (17,074), all members of the firm of Hill & Simpson, A Professional Corporation

Telephone: 312/876-0200 Ext. 3491
my attorneys with full power of substitution and revocation, to prosecute this application and to transact all
business in the Patent and Trademark Office connected therewith and direct that all correspondence be
forwarded to:

Hill & Simpson
A Professional Corporation
85th Floor Sears Tower, Chicago, Illinois 60606

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor GEORG-ERWIN ARNDT

Inventor's signature Georg Winkel Date 6.6.2000
Residence Erlangen, Germany
Citizenship Germany
Post Office Address Heinrich-Kirchnerstr. 32
91056 Erlangen, Germany

Full name of second joint inventor,
(if any)  **HARTMUT RITTER**

Full name of third joint inventor,
(if any) **ANTON GEBERT**

Inventor's signature Anton Wenz Date 6.6.2000
Residence Kleinsendelbach, Germany
Citizenship Germany
Post Office Address Hoehenroethstr. 11
91077 Kleinsendelbach, Germany